Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10002334	
Valid tyre size	VF 710 / 65 R 30 CFO +	
LI / SI / PR	179 A8	
TL/TT	TL	
Brand	Michelin	
Tread pattern	CerexBib 2	



Notes and features

- The Michelin Cerexbib 2 is a newly-developed tyre for . large harvesting machines.
- Its contact area, which is up to 15% larger than that of the • CerexBib, provides optimum soil protection.
- All Cerexbib 2 tyres are CFO tyres ans therefore suitable for cyclic field operations.
- The Cerexbib 2 has a special casing construction with -Ultraflex technology.
- This casing design enables up to 40 higher loading • capacities at the same inflation pressure for VF tyres.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10002334
EAN	3528706088148
Valid tyre size	VF 710 / 65 R 30 CFO +
LI / SI / PR	179 A8
TL/TT	TL
Brand	Michelin
Tread pattern	CerexBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	220,00
Recommended rim size	DW25B(A)
Permitted rim size	DW23B(A)
Maximum air pressure [bar].	2,80
Section width (mm)	694
Outer diameter of tyre [mm].	1676
Stat. radius (SLR) [mm]	735
Speed Radius Index (SRI)	800
Rolling circumference [mm].	4952
Contact area [cm²]	3443
Tread depth (mm)	48,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	630
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 A8	7750	40		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.