Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10002337	
Valid tyre size	VF 900 / 65 R 46	
LI / SI / PR	193 D / 189 E	
TL/TT	TL	
Brand	Michelin	
Tread pattern	AxioBib 2	



Notes and features

- The Michelin Axiobib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10002337
EAN	3528705894351
Valid tyre size	VF 900 / 65 R 46
LI / SI / PR	193 D / 189 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	520,00
Recommended rim size	DW30B(A)
Permitted rim size	MW30B(A), TW30B
Maximum air pressure [bar].	2,00
Section width (mm)	915
Outer diameter of tyre [mm].	2322
Stat. radius (SLR) [mm]	998
Speed Radius Index (SRI)	1100
Rolling circumference [mm].	6830
Contact area [cm²]	6762
Tread depth (mm)	74,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	1494.75
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
193 D	11500	65		2,00	
189 E	10300	70		2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.