# Bohnenkamp Moving Professionals

\_\_\_\_

### **TYRES**

Product group	Tyres	
Item number	10002338	
Valid tyre size	VF 750 / 75 R 46	
LI / SI / PR	189 D / 185 E	
TL/TT	TL	
Brand	Michelin	
Tread pattern	AxioBib 2	



#### Notes and features

- The Michelin Axiobib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10002338
EAN	3528703824725
Valid tyre size	VF 750 / 75 R 46
LI / SI / PR	189 D / 185 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	390,00
Recommended rim size	DW25B(A)
Maximum air pressure [bar].	2,00
Section width (mm)	762
Outer diameter of tyre [mm].	2288
Stat. radius (SLR) [mm]	1012
Speed Radius Index (SRI)	1100
Rolling circumference [mm].	6773
Contact area [cm²]	4998
Tread depth (mm)	740,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	1356
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
189 D	10300	65		2,00	
185 E	9250	70		2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.