

TYRES

Product group	Tyres	
Item number	10002340	
Valid tyre size	VF 650 / 65 R 38	
LI / SI / PR	172 D / 168 E	
TL/TT	TL	
Brand	Michelin	
Tread pattern	AxioBib 2	



Notes and features

- The Michelin Axiobib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.



Technical Informations

Item number	10002340
EAN	3528703515494
Valid tyre size	VF 650 / 65 R 38
LI / SI / PR	172 D / 168 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	240,00
Recommended rim size	DW23B(A)
Permitted rim size	DW21B(A), MW21B(A)
Maximum air pressure [bar].	2,00
Section width (mm)	682
Outer diameter of tyre [mm].	1816
Stat. radius (SLR) [mm]	791
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5388
Contact area [cm²]	3449
Tread depth (mm)	60,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	864
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 D	6300	65		2,00	
168 E	5600	70		2,00	