

TYRES

Product group	Tyres
Item number	10002340
Valid tyre size	VF 650 / 65 R 38
LI / SI / PR	172 D / 168 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2



Notes and features

- The Michelin AxioBib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

Technical Informations

Item number	10002340
EAN	3528703515494
Valid tyre size	VF 650 / 65 R 38
LI / SI / PR	172 D / 168 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	240,00
Recommended rim size	DW23B(A)
Permitted rim size	DW21B(A), MW21B(A)
Maximum air pressure [bar].	2,00
Section width (mm)	682
Outer diameter of tyre [mm].	1816
Stat. radius (SLR) [mm]	791
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5388
Contact area [cm ²]	3449
Tread depth (mm)	60,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	864
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 D	6300	65		2,00	
168 E	5600	70		2,00	