

TYRES

Product group	Tyres
Item number	10002346
Valid tyre size	14.9 - 28
LI / SI / PR	140 A8, 14 PR
TL/TT	тт
Brand	Nokian
Tread pattern	TR Forest
Sonderpostenkategorie	Remaining stock



Notes and features

- Reliable tyre for agricultural tractors used in forestry.
- The right choice for tractors used predominantly for forest work.
- Reliable, versatile and optimally geared to the vehicle type.
- Special rubber compound for use in forest cultivation.
- Strong bias construction.
- Good on- and off-road handling.
- Soil-protecting, self-cleaning tread pattern.



Technical Informations

Item number	10002346
EAN	4040658119484
Valid tyre size	14.9 - 28
LI / SI / PR	140 A8, 14 PR
TL/TT	тт
Brand	Nokian
Tread pattern	TR Forest
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	83,29
Recommended rim size	13
Permitted rim size	12, 11
Maximum air pressure [bar].	3,00
Section width (mm)	378
Outer diameter of tyre [mm].	1365
Stat. radius (SLR) [mm]	635
Rolling circumference [mm].	4065
Tyre capacity 75% [ltr.]	180
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		3,00	
		40			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.