Bohnenkamp Moving Professionals

14.11.2024

TYRES

Product group	Tyres	
Item number	10002347	
Valid tyre size	16.9 - 30	
LI / SI / PR	14 PR	
TL/TT	TT	
Brand	Nokian	
Tread pattern	TR Forest	
Sonderpostenkategorie	Remaining stock	



Notes and features

- Reliable tyre for agricultural tractors used in forestry.
- The right choice for tractors used predominantly for forest work.
- Reliable, versatile and optimally geared to the vehicle type.
- Special rubber compound for use in forest cultivation.
- Strong bias construction.
- Good on- and off-road handling.
- Soil-protecting, self-cleaning tread pattern.

Bohnenkamp Moving Professionals

Technical Informations

Iten numberi0002347EAN040658119491Valid tyre size05.9Li / Si / PR05.9Li / Si / PR70.0BrandNainaTread patternRF orestAristaticNoDiageovich (Liggen)9.42Recommender in size1.5Brand0.0Recommender in size1.6Diageovich (Lingen)0.0Brandmain (Ling		
Valid tyre size16.9 - 30Li / Si / PR4 PRTL/TTTTBrandNokianTread patternTR ForestAntistaticNoBlack9.942Nettogewicht [kg] (gültig)9.942Permitted rim size15Back30Maximum air pressure [back]2.90Outer diameter of tyre [m]3.93Section width [m]3.93Back3.93Bac	Item number	10002347
LI / SI / PRLI / SI / PRTL/T1TFrandNokianTread patternR ForestAntistaticNoYer colourBlackBecommended rim size9.42Permitted rim size14Antistatic14Section width (mm)2.90Section size (size)3.90Section size (size)3.90 </th <th>EAN</th> <th>4040658119491</th>	EAN	4040658119491
TLTTITTIFradNokianTread patternIR ForestAntistaticNoStarcolourBlackNettogewicht [kg] (gültig)9,42Permitted rim size16Maximum air pressure [back2,60Section width (mm)429Stat. radius (SLR) [mm]683Bating cirum ference [mm]633	Valid tyre size	16.9 - 30
BrandNokianTread patternR ForestAntistaticNoDiscBackTyre colourBackNetrogewicht [kg] (gittig)9,42Pernitted rim size15Pernitted rim size14Section width (mm)2,90Section size (statistic)3,80Section size (statistic)	LI / SI / PR	14 PR
Tread patternTR ForestAntistaticNoTyre colourBlackNettogewicht [kg] (üitig)9,42Recommended rim size15Pernitted rim size14Olde2,00Section width (mm)49Gate415Stat. radius (SLR) [mm]683Bottogewicht [kg] (mm)613	TL/TT	TT
AntistaticNoTyre colourBlackNettogewicht [kg] (gültig)99.42Recommended rim size15Permitted rim size14Saction width (mm)2.60Section width (mm)4.99Stat. radius (SLR) [m]6.33Bating circumference [m]4.361	Brand	Nokian
Tyre colourBackNettogewicht [kg] (gültig)99,42Recommended rim size15Permitted rim size14Section width (mm)2,60Section width (mm)429Outer diameter of tyre [mm]1485Stat. radius (SLR) [mm]683Back (Marcing Marcing Marc	Tread pattern	TR Forest
Nettogewicht [kg] (üiltig)9,42Recommended rim size15Permitted rim size14Maximun air pressure [ba]2,60Section width (mm)49Outer diameter of tyre [mm]1485Stat. radius (SLR) [mm]633Bolling circumference [mm]401	Antistatic	No
Recommended rim size15Permitted rim size14Maxinum air pressure [bar]2,00Section width (mm)429Outer diameter of tyre [mm]1485Stat. radius (SLR) [mm]633Aoling circumference [mm]4304	Tyre colour	Black
Permitted rim size14Maximum air pressure [bar]2,60Section width (mm)429Outer diameter of tyre [mm]1485Stat. radius (SLR) [mm]683Bolling circumference [mm]4361	Nettogewicht [kg] (gültig)	99,42
Maximum air pressure [bar] 2,60 Section width (mm) 429 Outer diameter of tyre [mm] 1485 Stat. radius (SLR) [mm] 683 Rolling circumference [mm] 4361	Recommended rim size	15
Section width (mm) 429 Outer diameter of tyre [mm] 1485 Stat. radius (SLR) [mm] 683 Rolling circumference [mm] 4361	Permitted rim size	14
Outer diameter of tyre [mm]. 1485 Stat. radius (SLR) [mm]. 683 Rolling circumference [mm]. 4361	Maximum air pressure [bar].	2,60
Stat. radius (SLR) [mm] 683 Rolling circumference [mm]. 4361	Section width (mm)	429
Rolling circumference [mm]. 4361	Outer diameter of tyre [mm].	1485
	Stat. radius (SLR) [mm]	683
E-Ready No	Rolling circumference [mm].	4361
	E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	2800	40		2,60	