

WHEELS

Product group	Wheels
Item number	10002353
Valid wheel size	400 / 70 R 20
Brand	Alliance
Tread pattern	Multiuse 550
Valid rim size	W 14 x 20
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	-60
Rim colour	Silver
Load capacity complete wheel [kg]	3250
Speed complete wheel [km/h]	50



Technical Informations

Assembly Item no. Tyres	• 15284045
LI / SI / PR	149 A8 / 149 B
Load capacity 1 [kg]	3250
Speed 1 [km/h].	40
Load capacity 2 [kg]	3250
Speed 2 [km/h].	50
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	102,79

ECE regulation number	ECE 106
Section width (mm)	404
Stat. radius (SLR) [mm]	482
Rolling circumference [mm].	3197
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	142
E-Ready	No
Assembly Item no. Rim	• 10001216
Load capacity of rim 1 [kg]	5300
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	4600
Speed Rims 2 [km/h]	30
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,00
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10.0
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8

Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27.0
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade