

WHEELS

Product group	Wheels
Item number	10002358
Valid wheel size	400 / 50 - 15
Brand	BKT
Tread pattern	AS 504
Valid rim size	13 LB x 15 H2
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-105
Rim colour	Silver
Load capacity complete wheel [kg]	1450
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15710565
LI / SI / PR	109 A8 / 121 A8, 8 PR
Load capacity 1 [kg]	1030
Speed 1 [km/h].	40
Load capacity 2 [kg]	1450
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	46,45
ECE regulation number	ECE 106
Section width (mm)	395

Stat. radius (SLR) [mm]	369
Rolling circumference [mm].	2387
Tread depth (mm)	19,5
Number of lugs	14x2
E-Ready	No
Assembly Item no. Rim	• 32010327
Load capacity of rim 1 [kg]	1485
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	2000
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,00
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	8
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere

Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade