

TYRES

Product group	Tyres
Item number	10002369
Valid tyre size	295 / 60 R 22.5
LI / SI / PR	150 / 147 L, 1PR
TL/TT	TL
Brand	Sailun
Tread pattern	SFR1+



 **SAILUN**
TYRE

Notes and features

- The Sailun SFR1+ is a truck tyre for the steering axle for multifunctional use in local and regional operations.
- The wide tread allows for slow, even wear and good handling.
- The optimised tread compound increases the tyre's service life.
- The SFR1+ has been further optimized compared to the SFR1 and the rubber compound has been improved.
- Its wide tyre shoulder and shoulder groove design ensure low rolling resistance and low fuel consumption.

Technical Informations

Item number	10002369
EAN	8935341203464
Valid tyre size	295 / 60 R 22.5
LI / SI / PR	150 / 147 L, 1PR
TL/TT	TL
Brand	Sailun
Tread pattern	SFR1+
M+S	M+S
3PMSF	3PMSF
Rolling resistance	C
Wet grip	B
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	49,21
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	295
Tread width (mm)	242
Outer diameter of tyre [mm].	926
Stat. radius (SLR) [mm]	435
Rolling circumference [mm].	2806
Tread depth (mm)	14,5

E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 L	3350	120	Single	9,00	
147 L	3075	120	Twin	9,00	