

TYRES

Product group	Tyres
Item number	10002370
Valid tyre size	295 / 60 R 22.5
LI / SI / PR	150 / 147 L, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDR1+



Bohnenkamp
■ ■ ● Moving Professionals

 **SAILUN**
TYRE

Notes and features

- The Sailun SDR1+ is a truck tyre for drive axles for local and regional traffic.
- The widened tread grooves provide good self-cleaning and good grip in all weather conditions.
- A rib runs between the tread blocks for improved rigidity and resulting reduced wear.
- Its wide contact area guarantees very good driving stability with optimum grip.
- Compared to the SDR1, the SDR1+ has been further optimized and the rubber compound has been improved.

Technical Informations

Item number	10002370
EAN	8935341203471
Valid tyre size	295 / 60 R 22.5
LI / SI / PR	150 / 147 L, 18 PR
TL/TT	TL
Brand	Sailun
Tread pattern	SDR1+
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	A
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	52,23
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	295
Tread width (mm)	260
Outer diameter of tyre [mm].	926
Stat. radius (SLR) [mm]	435
Rolling circumference [mm].	2806
Tread depth (mm)	17,0

E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 L	3350	120	Single	9,00	
147 L	3075	120	Twin	9,00	