Bohnenkamp Moving Professionals

19.11.2024

TYRES

Product group	Tyres
Item number	10002384
Valid tyre size	IF 650 / 75 R 38
LI / SI / PR	175 D / 171 E
TL/TT	TL
Brand	Kleber
Tread pattern	Topker IF



Technical Informations

Item number	10002384
EAN	3528709207249
Valid tyre size	IF 650 / 75 R 38
LI / SI / PR	175 D / 171 E
TL/TT	TL
Brand	Kleber
Tread pattern	Topker IF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	285,00
Recommended rim size	DW23B (A)

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Permitted rim size	DW21B (A), DW24B (A)
Maximum air pressure [bar].	2,40
Section width (mm)	688
Outer diameter of tyre [mm].	1932
Stat. radius (SLR) [mm]	859
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5726
Contact area [cm²]	3672
Tread depth (mm)	61,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	727.50
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 D	6900	65		2,40	
171 E	6150	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.