

## TYRES

Product group	Tyres
Item number	10002412
Valid tyre size	18.00 - 33
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	SM 54 M



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The smooth and extra deep L-4S tread is ideally suited to handling empty and loaded containers, especially on hard surfaces.
- The tread consists of a highly wear and cut resistant rubber compound.
- Compared to the predecessor SM 54, the SM 54 M tread is somewhat flatter for an even longer service life.
- The extra deep and smooth tread pattern provides for a wheel with highest driving comfort and outstanding stability during lift mode.

## Technical Informations

Item number	10002412
EAN	8903094074914
Valid tyre size	18.00 - 33
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	SM 54 M
TRA Code	IND4S
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	553,30
Permitted rim size	13.00/2.5
Maximum air pressure [bar].	10,00
Section width (mm)	535
Outer diameter of tyre [mm].	1895
Stat. radius (SLR) [mm]	840
Rolling circumference [mm].	5609
Tread depth (mm)	59,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	27000	10	Load wheel	10,00	
	21600	10	Steering wheel	10,00	