

RIMS

Product group	Rims
Item number	10002416
Valid rim size	DWW 18 x 42
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-334
Rim colour	Silver
Brand	Gruva



Technical Informations

Load capacity of rim 1 [kg]	4520
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4330
Speed Rims 2 [km/h]	50
Load capacity of rim 3 [kg]	4125
Speed Rims 3 [km/h]	65
Maximum speed [km/h].	50
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	212,00
Hump	kein Hump
Single / multi-part	einteilig

Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	16.0
Preassembled valve	No