

WHEELS

Product group	Wheels
Item number	10002417
Valid wheel size	600 / 60 R 30.5
Brand	Alliance
Tread pattern	882
Valid rim size	AG 20.00 x 30.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5800
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 10002136
LI / SI / PR	169 D
Load capacity 1 [kg]	5800
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	285,15
ECE regulation number	ECE 106
Section width (mm)	611
Stat. radius (SLR) [mm]	680.1

Speed Radius Index (SRI)	700
Rolling circumference [mm].	4518
Tread depth (mm)	25,0
Tyre capacity 75% [ltr.]	414.22
E-Ready	No
Assembly Item no. Rim	• 10001524
Load capacity of rim 1 [kg]	11250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8250
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade