

## WHEELS

Product group	Wheels
Item number	10002429
Valid wheel size	445 / 65 - 22.5
Brand	BKT
Tread pattern	MP 590
Valid rim size	14.00 x 22.5
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	-100
Rim colour	Silver
Load capacity complete wheel [kg]	4875
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15731230
LI / SI / PR	163 A8, 16 PR
Load capacity 1 [kg]	4875
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	143,60
ECE regulation number	ECE 106
Section width (mm)	480

Stat. radius (SLR) [mm]	530
Rolling circumference [mm].	3534
Tread depth (mm)	31,0
Number of lugs	18x2
E-Ready	No
Assembly Item no. Rim	• 10000802
Load capacity of rim 1 [kg]	6400
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,50
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27.0
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12
Ventilation holes	No
Verschweißung beidseitig	No

---

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade