

WHEELS

Product group	Wheels
Item number	10002451
Valid wheel size	31 x 15.50 - 15
Brand	BKT
Tread pattern	TR 313
Valid rim size	13 x 15
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	-85
Rim colour	Silver
Load capacity complete wheel [kg]	1250
Speed complete wheel [km/h]	50



Technical Informations

Assembly Item no. Tyres	• 15710552
LI / SI / PR	116 B, 8 PR
Load capacity 1 [kg]	1250
Speed 1 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	44,81
ECE regulation number	ECE 106
Section width (mm)	370
Stat. radius (SLR) [mm]	342
Rolling circumference [mm].	2233

Tread depth (mm)	23,5
Number of lugs	19x2
E-Ready	No
Assembly Item no. Rim	• 10001478
Load capacity of rim 1 [kg]	3300
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2800
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	3,10
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 DS 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16

hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade