

WHEELS

Product group	Wheels
Item number	10002457
Valid wheel size	405 / 70 R 20
Brand	BKT
Tread pattern	Multimax MP 538
Valid rim size	13 x 20
Rim connection	8/221/275
Bolt hole design	B2
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	3550
Speed complete wheel [km/h]	90
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 10000205
LI / SI / PR	152 G
Load capacity 1 [kg]	3550
Speed 1 [km/h].	90
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	116,24

ECE regulation number	ECE 54
Section width (mm)	407
Stat. radius (SLR) [mm]	484
Rolling circumference [mm].	3289
Tread depth (mm)	26,5
E-Ready	No
Assembly Item no. Rim	• 30812465
Load capacity of rim 1 [kg]	4250
Speed Rims 1 [km/h]	50
Load capacity of rim 2 [kg]	3550
Speed Rims 2 [km/h]	90
Maximum speed [km/h].	90
Maximum air pressure [bar].	6,00
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade