

## WHEELS

Product group	Wheels
Item number	10002499
Valid wheel size	600 / 50 - 22.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5150
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15212639
LI / SI / PR	153 A8 / 165 A8, 16 PR
Load capacity 1 [kg]	3650
Speed 1 [km/h].	40
Load capacity 2 [kg]	5150
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	166,68
ECE regulation number	ECE 106
Section width (mm)	600

Stat. radius (SLR) [mm]	518
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3542
Tread depth (mm)	40,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	250
E-Ready	No
Assembly Item no. Rim	• 33060413
Load capacity of rim 1 [kg]	7600
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5600
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,60
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27

---

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade