

WHEELS

| | |
|-----------------------------------|--------------------|
| Product group | Wheels |
| Item number | 10002506 |
| Valid wheel size | 650 / 50 R 22.5 |
| Brand | Alliance |
| Tread pattern | 885 |
| Valid rim size | AG 20.00 x 22.5 H2 |
| Rim connection | 10/281/335 |
| Bolt hole design | A3 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 4875 |
| Speed complete wheel [km/h] | 65 |



Technical Informations

| | |
|----------------------------|--------------|
| Assembly Item no. Tyres | • 15216249 |
| LI / SI / PR | 163 D |
| Load capacity 1 [kg] | 4875 |
| Speed 1 [km/h]. | 65 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 191,17 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 650 |
| Stat. radius (SLR) [mm] | 554 |

| | |
|-----------------------------|------------|
| Speed Radius Index (SRI) | 575 |
| Rolling circumference [mm]. | 3630 |
| Tread depth (mm) | 20,0 |
| Number of lugs | 27x2 |
| E-Ready | No |
| Assembly Item no. Rim | • 33060408 |
| Load capacity of rim 1 [kg] | 7600 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 5600 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 65 |
| Maximum air pressure [bar]. | 4,00 |
| Type of drive | Towed axle |
| Hump | H2 |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 10 |
| Bolt hole design EUWA | B22 ES 36 |
| Bolt hole diameter [mm] | 27 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |

| | |
|--------------------------------|----------------|
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| Valve design | Metal valve |
| Valve designation ETRTO | V5.01.1 |
| Valve length [mm] | 50.0 |
| Valve angle [°] | gerade |