

WHEELS

Product group	Wheels
Item number	10002522
Valid wheel size	340 / 80 R 18
Brand	Alliance
Tread pattern	585
Valid rim size	11 x 18
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+40
Rim colour	Anthrazit
Load capacity complete wheel [kg]	2725
Speed complete wheel [km/h]	50



Technical Informations

Assembly Item no. Tyres	• 15285410
LI / SI / PR	143 A8 / 143 B
Load capacity 1 [kg]	2725
Speed 1 [km/h].	40
Load capacity 2 [kg]	2725
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	85,25
ECE regulation number	ECE 106
Section width (mm)	345

Stat. radius (SLR) [mm]	454
Rolling circumference [mm].	2975
Tread depth (mm)	29,0
Number of lugs	24x2
E-Ready	No
Assembly Item no. Rim	• 33060120
Load capacity of rim 1 [kg]	3850
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	90
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL7016
Cavity Sealed	No
Disc thickness [mm]	12
Ventilation holes	No
Verschweißung beidseitig	No
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade