

WHEELS

Product group	Wheels
Item number	10002524
Valid wheel size	600 / 50 - 22.5
Brand	Nokian
Tread pattern	Excavator
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	10/281/335
Offset (mm)	-14
Rim colour	Grey
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 17412112
LI / SI / PR	173 A8, 24 PR
Load capacity 1 [kg]	6500
Speed 1 [km/h].	40
Carcass properties	SF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	206,63
ECE regulation number	not necessary
Section width (mm)	600

Stat. radius (SLR) [mm]	523
Rolling circumference [mm].	3531
Tread depth (mm)	40,0
E-Ready	No
Assembly Item no. Rim	• 10002321
Load capacity of rim 1 [kg]	9000
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6650
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	6,00
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	25.4
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	HB
Rim material	steel
RAL	RAL7024
Cavity Sealed	No
Disc thickness [mm]	12
Knurling	with knurling
Ventilation holes	No
Verschweißung beidseitig	No

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade