

## WHEELS

|                                   |                    |
|-----------------------------------|--------------------|
| Product group                     | Wheels             |
| Item number                       | 10002535           |
| Valid wheel size                  | 710 / 50 R 26.5    |
| Brand                             | BKT                |
| Tread pattern                     | FL 630 Ultra       |
| Valid rim size                    | AG 24.00 x 26.5 H2 |
| Rim connection                    | 10/281/335         |
| Bolt hole design                  | A3                 |
| Rim colour                        | Silver             |
| Load capacity complete wheel [kg] | 8250               |
| Speed complete wheel [km/h]       | 40                 |
| RDRA (Reifendruckregelanlage)     | No                 |
| RDKS (Reifendruckkontrollsystem)  | No                 |



## Technical Informations

|                            |                |
|----------------------------|----------------|
| Assembly Item no. Tyres    | • 15715221     |
| LI / SI / PR               | 181 A8 / 170 D |
| Load capacity 1 [kg]       | 8250           |
| Speed 1 [km/h].            | 40             |
| Load capacity 2 [kg]       | 6000           |
| Speed 2 [km/h].            | 65             |
| Antistatic                 | No             |
| Tyre colour                | Black          |
| Nettogewicht [kg] (gültig) | 267,66         |
| ECE regulation number      | ECE 106        |

|                                |                               |
|--------------------------------|-------------------------------|
| Section width (mm)             | 727                           |
| Stat. radius (SLR) [mm]        | 599                           |
| Speed Radius Index (SRI)       | 650                           |
| Rolling circumference [mm].    | 4208                          |
| Tread depth (mm)               | 30,5                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 33060570                    |
| Load capacity of rim 1 [kg]    | 9650                          |
| Speed Rims 1 [km/h]            | 40                            |
| Load capacity of rim 2 [kg]    | 7100                          |
| Speed Rims 2 [km/h]            | 65                            |
| Maximum speed [km/h].          | 65                            |
| Maximum air pressure [bar].    | 4,00                          |
| Number of bolt holes           | 10                            |
| Bolt hole design EUWA          | B22 ES 36                     |
| hub hole diameter [mm].        | 281                           |
| Bolt hole circle diameter [mm] | 335                           |
| Bolt hole diameter [mm]        | 27                            |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R18                           |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | H2                            |
| Valve protection               | VSH                           |
| Single / multi-part            | einteilig                     |
| Rim centering                  | BC                            |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |

---

|                          |                |
|--------------------------|----------------|
| Cavity Sealed            | No             |
| Ventilation holes        | No             |
| Verschweißung beidseitig | No             |
| Valve seat               | External Valve |
| Valve hole diameter [mm] | 15.7           |
| Preassembled valve       | No             |
| TPMS-kompatibles Ventil  | No             |
| Valve design             | Metal valve    |
| Valve designation ETRTO  | V5.01.1        |
| Valve length [mm]        | 50.0           |
| Valve angle [°]          | gerade         |