

WHEELS

Product group	Wheels
Item number	10002540
Valid wheel size	550 / 45 - 22.5
Brand	BKT
Tread pattern	Flotation 648 T
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A2
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5300
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712532
LI / SI / PR	154 A8 / 166 A8, 20 PR
Load capacity 1 [kg]	3750
Speed 1 [km/h].	40
Load capacity 2 [kg]	5300
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	134,99

ECE regulation number	ECE 106
Section width (mm)	550
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3203
Tread depth (mm)	22,0
Number of lugs	26x2
E-Ready	No
Assembly Item no. Rim	• 33060352
Load capacity of rim 1 [kg]	5600
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,00
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VSV
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Air-water valve
Valve length [mm]	47
Valve angle [°]	gerade
Colour of cap	Black
Valve cap Material	Plastic