

## WHEELS

Product group	Wheels
Item number	10002543
Valid wheel size	10 - 16.5
Brand	BKT
Tread pattern	Skid Power SK
Valid rim size	8.25 x 16.5
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	1400
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15772121
LI / SI / PR	120 A8, 10 PR
Load capacity 1 [kg]	1400
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	42,98
ECE regulation number	ECE 106
Section width (mm)	270

Stat. radius (SLR) [mm]	355
Rolling circumference [mm].	2286
Tread depth (mm)	15,0
E-Ready	No
Assembly Item no. Rim	• 10002443
Load capacity of rim 1 [kg]	4000
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3400
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,20
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10

---

<b>Knurling</b>	without knurling
<b>Ventilation holes</b>	No
<b>Verschweißung beidseitig</b>	No
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>TPMS-kompatibles Ventil</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V3.21.1
<b>Valve length [mm]</b>	33.0
<b>Valve angle [°]</b>	gerade