

WHEELS

Product group	Wheels
Item number	10002570
Valid wheel size	435 / 50 R 19.5
Brand	Sailun
Tread pattern	STL1
Valid rim size	14.00 x 19.5
Rim connection	10/176/225
Bolt hole design	M22
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	100



 **SAILUN**
TYRE

Technical Informations

Assembly Item no. Tyres	• 11066241
LI / SI / PR	160 J, 20 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	114,70
ECE regulation number	ECE 54 ECE 117

Section width (mm)	438
Stat. radius (SLR) [mm]	430.64
Rolling circumference [mm].	2656
Tread depth (mm)	12,5
Rolling resistance	B
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 31267921
Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	176

Bolt hole circle diameter [mm]	225
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade