

WHEELS

Product group	Wheels
Item number	10002574
Valid wheel size	15.0 / 70 - 18
Brand	Alliance
Tread pattern	320
Valid rim size	13 x 18
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3450
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212405
LI / SI / PR	151 A8 / 147 B, 16 PR
Load capacity 1 [kg]	3450
Speed 1 [km/h].	40
Load capacity 2 [kg]	3075
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	77,23
ECE regulation number	ECE 106
Section width (mm)	391

Stat. radius (SLR) [mm]	442
Rolling circumference [mm].	2902
Tread depth (mm)	12,0
E-Ready	No
Assembly Item no. Rim	• 33060084
Load capacity of rim 1 [kg]	4450
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3850
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,25
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade