

## WHEELS

Product group	Wheels
Item number	10002594
Valid wheel size	650 / 55 R 26.5
Brand	Alliance
Tread pattern	380
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	6000
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15215700
LI / SI / PR	170 D / 167 E
Load capacity 1 [kg]	6000
Speed 1 [km/h].	65
Load capacity 2 [kg]	5450
Speed 2 [km/h].	70
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	235,10
ECE regulation number	ECE 106

Section width (mm)	645
Stat. radius (SLR) [mm]	618
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4175
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	535
E-Ready	No
Assembly Item no. Rim	• 10001302
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	70
Maximum air pressure [bar].	4,00
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10

---

<b>Bolt hole design EUWA</b>	B22 DS 36
<b>Bolt hole diameter [mm]</b>	27.0
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	281
<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade