

WHEELS

Product group	Wheels
Item number	10002596
Valid wheel size	205 / 65 R 17.5
Brand	Linglong
Tread pattern	LFL866
Valid rim size	6.00 x 17.5
Rim connection	10/176/225
Bolt hole design	M22
Offset (mm)	+113
Half centre distance (HMA) [mm]	125
Rim colour	Silver
Load capacity complete wheel [kg]	1850
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres	• 11366100
LI / SI / PR	129 / 127 J (132 / 132 G), 16 PR
Load capacity 1 [kg]	1850
Speed 1 [km/h].	100
Load capacity 2 [kg]	2000
Speed 2 [km/h].	90
Load capacity 3 [kg]	1750
Speed 3 [km/h].	100
Load capacity 4 [kg]	2000
Speed 4 [km/h].	90

M+S	M+S
3PMSF	3PMSF
Axle position truck	FA TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	53,40
ECE regulation number	ECE 54 ECE 117
Section width (mm)	205
Stat. radius (SLR) [mm]	334
Dynamic radius [mm]	342.87
Rolling circumference [mm].	2154
Tread depth (mm)	12,5
Rolling resistance	E
Wet grip	B
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 10001109
Load capacity of rim 1 [kg]	2725
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Disc thickness [mm]	12.0
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	10
Bolt hole diameter [mm]	26.0
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No