

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 10002611 |
| Valid wheel size | 385 / 65 R 22.5 |
| Brand | Sailun |
| Tread pattern | STR1+ |
| Valid rim size | 11.75 x 22.5 H |
| Rim connection | 10/281/335 |
| Bolt hole design | M22 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 5000 |
| Speed complete wheel [km/h] | 110 |



Bohnenkamp
■ ■ ● Moving Professionals

 **SAILUN**
TYRE

Technical Informations

| | |
|-------------------------|----------------------|
| Assembly Item no. Tyres | • 11066377 |
| LI / SI / PR | 164 K (158 L), 20 PR |
| Load capacity 1 [kg] | 5000 |
| Speed 1 [km/h]. | 110 |
| Load capacity 2 [kg] | 4250 |
| Speed 2 [km/h]. | 120 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | TR |
| Antistatic | No |
| Tyre colour | Black |

| | |
|-----------------------------|----------------------------------|
| Nettogewicht [kg] (gültig) | 120,40 |
| ECE regulation number | ECE 54 ECE 117 Vecto Certificate |
| Section width (mm) | 385 |
| Rolling circumference [mm]. | 3248 |
| Tread depth (mm) | 16,0 |
| Rolling resistance | C |
| Wet grip | C |
| Rolling noise [db]. | 72 |
| Rolling noise level | B |
| E-Ready | No |
| Assembly Item no. Rim | • 10000370 |
| Load capacity of rim 1 [kg] | 5000 |
| Speed Rims 1 [km/h] | 130 |
| Maximum speed [km/h]. | 120 |
| Maximum air pressure [bar]. | 9,00 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Disc thickness [mm] | 11 |
| Ventilation holes | Yes |
| Verschweißung beidseitig | No |
| Rim centering | HB |
| Number of bolt holes | 10 |
| Bolt hole diameter [mm] | 26.0 |

| | |
|--------------------------------|----------------|
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 9.7 |
| Preassembled valve | No |