## Bohnenkamp Moving Professionals

22.09.2024

## RIMS

Product group	Rims
Item number	10002617
Valid rim size	9.00 x 15.3
Rim connection	5/66.5/112
Bolt hole design	A1
Rim colour	Silver
Brand	Jantsa





## Load capacity of rim 1 [kg] 2700 Speed Rims 1 [km/h] 25 Load capacity of rim 2 [kg] 2300 Speed Rims 2 [km/h] 40 Load capacity of rim 3 [kg] 2850 Speed Rims 3 [km/h] 20 Load capacity of rim 4 [kg] 2550 Speed of wheels 4 [km/h]. 30 40 Maximum speed [km/h]. Type of drive Angetriebene & gezogene Achse Nettogewicht [kg] (gültig) 16,00

**Technical Informations** 

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

Нитр	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	8
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	66.5
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.