Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres	
Item number	10002646	
Valid tyre size	315 / 60 R 22.5	
LI / SI / PR	152 / 148 L, 18 PR	
TL/TT	TL	
Brand	Sailun	
Tread pattern	SDL2	





Technical Informations Item number 10002646 EAN 8935341201453 Valid tyre size 315 / 60 R 22.5 LI / SI / PR 152 / 148 L, 18 PR TL/TT ΤL Brand Sailun **Tread pattern** SDL2 M+S M+S 3PMSF 3PMSF Axle position truck RA В **Rolling resistance**

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Wet grip	В
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	58,00
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	313
Tread width (mm)	280
Outer diameter of tyre [mm].	950
Stat. radius (SLR) [mm]	445
Rolling circumference [mm].	2879
Tread depth (mm)	15,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,00	
148 L	3150	120	Twin	9,00	