

## WHEELS

|                                   |                     |
|-----------------------------------|---------------------|
| Product group                     | Wheels              |
| Item number                       | 10002648            |
| Valid wheel size                  | 385 / 65 R 22.5     |
| Brand                             | Bohnenkamp          |
| Tread pattern                     | Boka Agrar Trans II |
| Valid rim size                    | 11.75 x 22.5        |
| Rim connection                    | 6/161/205           |
| Bolt hole design                  | A2                  |
| Rim colour                        | Silver              |
| Load capacity complete wheel [kg] | 4500                |
| Speed complete wheel [km/h]       | 80                  |
| RDRA (Reifendruckregelanlage)     | No                  |
| RDKS (Reifendruckkontrollsystem)  | No                  |



## Technical Informations

|                            |                   |
|----------------------------|-------------------|
| Assembly Item no. Tyres    | • 19968044        |
| LI / SI / PR               | 160 F             |
| Load capacity 1 [kg]       | 4500              |
| Speed 1 [km/h].            | 80                |
| Antistatic                 | No                |
| Tyre colour                | Black             |
| Nettogewicht [kg] (gültig) | 128,95            |
| ECE regulation number      | not necessary     |
| Type of retreading         | Hot retreaded ECO |
| Section width (mm)         | 379               |

|                                |                |
|--------------------------------|----------------|
| Stat. radius (SLR) [mm]        | 496            |
| E-Ready                        | No             |
| Assembly Item no. Rim          | • 33060275     |
| Load capacity of rim 1 [kg]    | 6250           |
| Speed Rims 1 [km/h]            | 40             |
| Load capacity of rim 2 [kg]    | 5200           |
| Speed Rims 2 [km/h]            | 80             |
| Maximum speed [km/h].          | 80             |
| Maximum air pressure [bar].    | 8,50           |
| Number of bolt holes           | 6              |
| hub hole diameter [mm].        | 161            |
| Bolt hole circle diameter [mm] | 205            |
| Bolt hole diameter [mm]        | 21.5           |
| Countersinking                 | Sphere         |
| Spherical countersink [mm].    | R16            |
| Hump                           | kein Hump      |
| Valve protection               | VSH            |
| Single / multi-part            | einteilig      |
| Rim centering                  | BC             |
| Rim material                   | steel          |
| RAL                            | RAL9006        |
| Cavity Sealed                  | No             |
| Ventilation holes              | No             |
| Verschweißung beidseitig       | No             |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 15.7           |
| Preassembled valve             | No             |

---

|                         |             |
|-------------------------|-------------|
| TPMS-kompatibles Ventil | No          |
| Valve design            | Metal valve |
| Valve designation ETRTO | V5.01.1     |
| Valve length [mm]       | 50.0        |
| Valve angle [°]         | gerade      |