

WHEELS

Product group	Wheels
Item number	10002655
Valid wheel size	330 / 40 B 12
Brand	Carlisle
Tread pattern	Ultra Trac
Valid rim size	10.50 I x 12 H2
Rim connection	5/66.6/112
Bolt hole design	E1
Rim colour	Silver
Load capacity complete wheel [kg]	800
Speed complete wheel [km/h]	20



Technical Informations

Assembly Item no. Tyres	• 12500595
LI / SI / PR	100 A4, 4 PR
Load capacity 1 [kg]	800
Speed 1 [km/h].	20
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	22,82
ECE regulation number	ECE 106
Section width (mm)	328
Stat. radius (SLR) [mm]	259
Rolling circumference [mm].	1725

Tread depth (mm)	7,1
E-Ready	No
Assembly Item no. Rim	• 31610062
Load capacity of rim 1 [kg]	1100
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	1000
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	20
Maximum air pressure [bar].	1,24
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	66.6
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No

Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade