

## WHEELS

|                                   |                   |
|-----------------------------------|-------------------|
| Product group                     | Wheels            |
| Item number                       | 10002663          |
| Valid wheel size                  | 385 / 65 R 22.5   |
| Brand                             | Bohnenkamp        |
| Tread pattern                     | RE Power WP Truck |
| Valid rim size                    | 11.75 x 22.5 H    |
| Rim connection                    | 10/281/335        |
| Bolt hole design                  | B33               |
| Rim colour                        | Silver            |
| Load capacity complete wheel [kg] | 4500              |
| Speed complete wheel [km/h]       | 110               |



Bohnenkamp  
■ ■ ● Moving Professionals

## Technical Informations

|                            |                   |
|----------------------------|-------------------|
| Assembly Item no. Tyres    | • 19968076        |
| LI / SI / PR               | 160 K             |
| Load capacity 1 [kg]       | 4500              |
| Speed 1 [km/h].            | 110               |
| M+S                        | M+S               |
| 3PMSF                      | 3PMSF             |
| Antistatic                 | No                |
| Tyre colour                | Black             |
| Nettogewicht [kg] (gültig) | 112,28            |
| ECE regulation number      | ECE 109           |
| Type of retreading         | Hot retreaded ECO |

|                                |                               |
|--------------------------------|-------------------------------|
| Section width (mm)             | 385                           |
| Tread depth (mm)               | 16,0                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 10000369                    |
| Load capacity of rim 1 [kg]    | 5000                          |
| Speed Rims 1 [km/h]            | 130                           |
| Maximum speed [km/h].          | 110                           |
| Maximum air pressure [bar].    | 9,00                          |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | H                             |
| Single / multi-part            | einteilig                     |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |
| Disc thickness [mm]            | 11                            |
| Ventilation holes              | Yes                           |
| Verschweißung beidseitig       | No                            |
| Rim centering                  | BHC                           |
| Number of bolt holes           | 10                            |
| Bolt hole diameter [mm]        | 26.0                          |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R18                           |
| hub hole diameter [mm].        | 281                           |
| Bolt hole circle diameter [mm] | 335                           |
| Valve seat                     | External Valve                |
| Valve hole diameter [mm]       | 9.7                           |
| Preassembled valve             | No                            |