Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	10002676
Valid rim size	6.75 x 22.5
Rim connection	8/221/275
Bolt hole design	M20
Offset (mm)	+144
Half centre distance (HMA) [mm]	156
Rim colour	Silver
Brand	Jantsa





Technical Informations

Load capacity of rim 1 [kg]	3100
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	39,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	НВ
Number of bolt holes	8
Bolt hole design EUWA	M20
Bolt hole diameter [mm]	24
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No