

TYRES

Product group	Tyres
Item number	10002679
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	165 D
TL/TT	TL
Brand	BKT
Tread pattern	Power Trailer SR331



Notes and features

- The BKT Power Trailer SR331 is an all-steel radial tyre for agricultural trailers and tankers in transport applications.
- When used in the field, it is characterised by very good flotation properties.
- On the road or other paved surfaces, the tyre scores with excellent traction.
- Its block tread ensures low rolling resistance, even pressure distribution on the ground and a comfortable ride.
- Thanks to its steel carcass, the tyre offers a high load capacity, exceptional stability and a long service life.
- The side wall is reinforced by a special rib and is therefore well protected against damage caused by knocks or chafing.
- The tyre sits perfectly on the rim thanks to the hexagonal reinforced bead.

Technical Informations

Item number	10002679
EAN	8903094073962
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	165 D
TL/TT	TL
Brand	BKT
Tread pattern	Power Trailer SR331
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	141,01
Recommended rim size	AG16.00
Permitted rim size	AG18.00
Maximum air pressure [bar].	5,00
Section width (mm)	555
Outer diameter of tyre [mm].	1245
Stat. radius (SLR) [mm]	565
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3775
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		5,00	