# Bohnenkamp Moving Professionals

20.09.2024

### TYRES

Product group	Tyres
Item number	10002680
Valid tyre size	14.9 - 24
LI / SI / PR	128 A8, 8 PR
TL/TT	TL
Brand	Alliance
Tread pattern	329





#### Notes and features

- Popular golf tread pattern for towed vehicles.
- Gentle on the soil.

• Also for tractors and road construction.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10002680
EAN	8903635001928
Valid tyre size	14.9 - 24
LI / SI / PR	128 A8, 8 PR
TL/TT	TL
Brand	Alliance
Tread pattern	329
TRA Code	R3
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	56,80
Recommended rim size	W13, W12
Maximum air pressure [bar].	2,10
Section width (mm)	394
Outer diameter of tyre [mm].	1241
Stat. radius (SLR) [mm]	574.3
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3700
Contact area [cm²]	1008.9
Tread depth (mm)	21,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	138.75
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 A8	1800	40		2,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.