

TYRES

Product group	Tyres
Item number	10002682
Valid tyre size	6.00 - 16
LI / SI / PR	94 A6, 8 PR
TL/TT	тт
Brand	Alliance
Tread pattern	FarmPRO 324



Notes and features

- The Alliance FarmPro 324 has a modern 45 degree lug angle design, suitable for field and road applications.
- In field use, the tyre is characterised by very good traction.
- The revised, new-look tread pattern provides excellent self-cleaning properties.
- Its particularly resistant rubber compound prevents the enlargement of minor punctures.
- The complete R-1 range is available with this tread pattern.



Technical Informations

Item number	10002682
EAN	8903635021131
Valid tyre size	6.00 - 16
LI / SI / PR	94 A6, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	FarmPRO 324
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	9,60
Recommended rim size	4.5E
Maximum air pressure [bar].	4,50
Section width (mm)	165
Outer diameter of tyre [mm].	735
Stat. radius (SLR) [mm]	349.1
Speed Radius Index (SRI)	350
Rolling circumference [mm].	2172
Contact area [cm²]	151.2
Tread depth (mm)	18,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	21.53
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
94 A6	670	30		4,50	