

RIMS

Product group	Rims
Item number	10002699
Valid rim size	6.75 x 17.5
Rim connection	6/161/205
Rim colour	Black
Brand	Covex



Technical Informations

Load capacity of rim 1 [kg]	2100
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3135
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	25,61
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Disc thickness [mm]	11.75
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	внс
Number of bolt holes	6
Bolt hole diameter [mm]	21
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation	TR 501
Valve length [mm]	42.0