

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 10002706 |
| Valid tyre size | 650 / 65 R 42 |
| LI / SI / PR | 165 D / 161 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | RoadBib |



Notes and features

- The Michelin Roadbib is a radial tractor tyre for use in the field and on the road, with at least 80% on roads.
- Its large contact area ensures even ground pressure distribution, low rolling resistance and consequently low fuel consumption.
- The special tread pattern with the continuous central bar enables a high level of running smoothness and very good ride comfort when driving on the road.

Technical Informations

| | |
|------------------------------|--------------------|
| Item number | 10002706 |
| EAN | 3528700756432 |
| Valid tyre size | 650 / 65 R 42 |
| LI / SI / PR | 165 D / 161 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | RoadBib |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 250,00 |
| Recommended rim size | DW20B(A) |
| Permitted rim size | DW21B(A), DW23B(A) |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 633 |
| Outer diameter of tyre [mm]. | 1932 |
| Stat. radius (SLR) [mm] | 870 |
| Rolling circumference [mm]. | 5733 |
| Tread depth (mm) | 43,0 |
| Number of lugs | 23x2 |
| Tyre capacity 75% [ltr.] | 643 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 165 D | 5150 | 65 | | 2,40 | |
| 161 E | 4625 | 70 | | 2,40 | |