Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10002707	
Valid tyre size	650 / 65 R 34	
LI / SI / PR	161 D / 157 E	
TL/TT	TL	
Brand	Michelin	
Tread pattern	RoadBib	



Notes and features

- The Michelin Roadbib is a radial tractor tyre for use in the field and on the road, with at least 80% on roads.
- Its large contact area ensures even ground pressure distribution, low rolling resistance and consequently low fuel consumption.
- The special tread pattern with the continuous central bar enables a high level of running smoothness and very good ride comfort when driving on the road.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10002707
EAN	3528703303787
Valid tyre size	650 / 65 R 34
LI / SI / PR	161 D / 157 E
TL/TT	ТL
Brand	Michelin
Tread pattern	RoadBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	230,00
Recommended rim size	DW20B(A)
Permitted rim size	DW21B(A), DW23B(A)
Maximum air pressure [bar].	2,40
Section width (mm)	674
Outer diameter of tyre [mm].	1707
Stat. radius (SLR) [mm]	785
Rolling circumference [mm].	5098
Tread depth (mm)	39,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	555
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 D	4625	65		2,40	
157 E	4125	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.