

## WHEELS

Product group	Wheels
Item number	10002736
Valid wheel size	275 / 70 R 22.5
Brand	Sailun
Tread pattern	SAR1
Valid rim size	8.25 x 22.5 H
Rim connection	10/281/335
Bolt hole design	B33
Offset (mm)	+156
Half centre distance (HMA) [mm]	169
Rim colour	Silver
Load capacity complete wheel [kg]	3150
Speed complete wheel [km/h]	130



 **SAILUN**  
TYRE

## Technical Informations

Assembly Item no. Tyres	• 11066312
LI / SI / PR	148 / 145 M, 16 PR
Load capacity 1 [kg]	3150
Speed 1 [km/h].	130
Load capacity 3 [kg]	2900
Speed 3 [km/h].	130
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA TR
Antistatic	No

Tyre colour	Black
Nettogewicht [kg] (gültig)	88,37
ECE regulation number	ECE 54 ECE 117 Vecto Certificate
Section width (mm)	275
Stat. radius (SLR) [mm]	445.18
Rolling circumference [mm].	2801
Tread depth (mm)	14,5
Rolling resistance	C
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
E-Ready	No
Assembly Item no. Rim	• 10000367
Load capacity of rim 1 [kg]	3600
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	BC

---

Number of bolt holes	10
Bolt hole diameter [mm]	26.0
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No