

WHEELS

Product group	Wheels
Item number	10002744
Valid wheel size	400 / 60 - 15.5
Brand	BKT
Tread pattern	AW 708
Valid rim size	13.00 x 15.5
Rim connection	10/176/225
Bolt hole design	A3
Offset (mm)	-15
Rim colour	Silver
Load capacity complete wheel [kg]	3250
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711822
LI / SI / PR	149 A8, 18 PR
Load capacity 1 [kg]	3250
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	58,76
ECE regulation number	ECE 106
Section width (mm)	405

Stat. radius (SLR) [mm]	380
Rolling circumference [mm].	2564
Tread depth (mm)	12,0
E-Ready	No
Assembly Item no. Rim	• 33060113
Load capacity of rim 1 [kg]	4450
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3750
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,50
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade