

WHEELS

Product group	Wheels
Item number	10002777
Valid wheel size	215 / 75 - 17.5
Brand	BKT
Tread pattern	Rib Master
Valid rim size	6.75 x 17.5
Rim connection	8/221/275
Bolt hole design	M22
Offset (mm)	+130
Rim colour	Silver
Load capacity complete wheel [kg]	2650
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712440
LI / SI / PR	142 A8, 16 PR
Load capacity 1 [kg]	2650
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	44,39
ECE regulation number	ECE 106
Section width (mm)	220

Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2310
Tread depth (mm)	11,0
E-Ready	No
Assembly Item no. Rim	• 33060069
Load capacity of rim 1 [kg]	2750
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	40
Maximum air pressure [bar].	9,00
Number of bolt holes	8
Bolt hole design EUWA	M22
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	26
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	HB
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	Internal Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No

Valve design	Metal valve
Valve length [mm]	54.0
Valve angle [°]	36