

## WHEELS

|                                   |                  |
|-----------------------------------|------------------|
| Product group                     | Wheels           |
| Item number                       | 10002778         |
| Valid wheel size                  | 11.5 / 80 - 15.3 |
| Brand                             | BKT              |
| Tread pattern                     | AW 702           |
| Valid rim size                    | 9.00 x 15.3      |
| Rim connection                    | 6/161/205        |
| Bolt hole design                  | E2               |
| Offset (mm)                       | -5               |
| Rim colour                        | Silver           |
| Load capacity complete wheel [kg] | 1950             |
| Speed complete wheel [km/h]       | 40               |
| RDRA (Reifendruckregelanlage)     | No               |
| RDKS (Reifendruckkontrollsystem)  | No               |



Bohnenkamp  
■ ■ ● Moving Professionals

**BKT**  
GROWING TOGETHER

## Technical Informations

|                            |               |
|----------------------------|---------------|
| Assembly Item no. Tyres    | • 15711790    |
| LI / SI / PR               | 131 A8, 10 PR |
| Load capacity 1 [kg]       | 1950          |
| Speed 1 [km/h].            | 40            |
| Antistatic                 | No            |
| Tyre colour                | Black         |
| Nettogewicht [kg] (gültig) | 35,30         |
| ECE regulation number      | ECE 106       |
| Section width (mm)         | 297           |

|                                |            |
|--------------------------------|------------|
| Stat. radius (SLR) [mm]        | 370        |
| Rolling circumference [mm].    | 2473       |
| Tread depth (mm)               | 10,0       |
| E-Ready                        | No         |
| Assembly Item no. Rim          | • 31810196 |
| Load capacity of rim 1 [kg]    | 3150       |
| Speed Rims 1 [km/h]            | 25         |
| Load capacity of rim 2 [kg]    | 2650       |
| Speed Rims 2 [km/h]            | 40         |
| Maximum speed [km/h].          | 40         |
| Maximum air pressure [bar].    | 3,40       |
| Number of bolt holes           | 6          |
| hub hole diameter [mm].        | 161        |
| Bolt hole circle diameter [mm] | 205        |
| Bolt hole diameter [mm]        | 21.5       |
| Countersinking                 | Sphere     |
| Spherical countersink [mm].    | R16        |
| Type of drive                  | Towed axle |
| Hump                           | kein Hump  |
| Valve protection               | VSH        |
| Single / multi-part            | einteilig  |
| Rim centering                  | BC         |
| Rim material                   | steel      |
| RAL                            | RAL9006    |
| Cavity Sealed                  | No         |
| Number of drain holes          | 2          |
| Ventilation holes              | No         |

---

|                          |                |
|--------------------------|----------------|
| Verschweißung beidseitig | No             |
| Valve seat               | External Valve |
| Valve hole diameter [mm] | 15.7           |
| Preassembled valve       | No             |
| TPMS-kompatibles Ventil  | No             |
| Valve design             | Rubber valve   |
| Valve designation ETRTO  | V2.03.3        |
| Valve length [mm]        | 43.0           |
| Valve angle [°]          | gerade         |