

RIMS

Product group	Rims
Item number	10002801
Valid rim size	11.25 - 25 / 2.0
Rim connection	24/371/425
Bolt hole design	M20
Offset (mm)	+85
Rim colour	Black
Brand	Jamak

Technical Informations

Load capacity of rim 1 [kg]	16900
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	15300
Speed Rims 2 [km/h]	30
Load capacity of rim 3 [kg]	15625
Speed Rims 3 [km/h]	25
Load capacity of rim 4 [kg]	7300
Speed of wheels 4 [km/h].	50
Maximum speed [km/h].	50
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	167,60

Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	five-part
Rim material	steel
RAL	RAL9005
Colour type	Glossy
Cavity Sealed	No
Rim design industry	Standard
Rim flange height [inch]	2.0
Disc thickness [mm]	18
Knurling	with knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	24
Bolt hole design EUWA	M20
Bolt hole diameter [mm]	24.0
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Valve hole diameter [mm]	20.5
Preassembled valve	No