Bohnenkamp Moving Professionals

WHEELS

Product group	Wheels
Item number	10002864
Valid wheel size	4.80 / 4.00 - 8
Brand	Deli
Tread pattern	S-380
Valid rim size	2.50 A x 8 H2
Rim connection	4/63/100
Rim colour	Silver
Load capacity complete wheel [kg]	335
Speed complete wheel [km/h]	130



Technical Informations

Assembly Item no. Tyres	19166105
LI / SI / PR	70 M, 6 PR
Load capacity 1 [kg]	335
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	5,87
ECE regulation number	ECE 54
Section width (mm)	119
Stat. radius (SLR) [mm]	195
Rolling circumference [mm].	1286

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp

Moving Professionals

Tread depth (mm)	5,0
E-Ready	No
Assembly Item no. Rim	39600306
Load capacity of rim 1 [kg]	345
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	130
Maximum air pressure [bar].	5,00
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	14.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	63
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Valve length [mm]	43.0
Valve angle [°]	gerade

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.