

WHEELS

Product group	Wheels
Item number	10002881
Valid wheel size	365 / 70 R 18
Brand	BKT
Tread pattern	Multimax MP 513
Valid rim size	11 x 18
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+20
Rim colour	Silver
Load capacity complete wheel [kg]	2060
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15735226
LI / SI / PR	133 G
Load capacity 1 [kg]	2060
Speed 1 [km/h].	90
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	78,28
ECE regulation number	ECE 54

Section width (mm)	360
Stat. radius (SLR) [mm]	448
Rolling circumference [mm].	2954
Tread depth (mm)	28,5
Number of lugs	18x2
E-Ready	No
Assembly Item no. Rim	• 33060119
Load capacity of rim 1 [kg]	3850
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2350
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,75
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Disc thickness [mm]	12.0
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade