

## WHEELS

|                                   |                 |
|-----------------------------------|-----------------|
| Product group                     | Wheels          |
| Item number                       | 10002882        |
| Valid wheel size                  | 365 / 70 R 18   |
| Brand                             | BKT             |
| Tread pattern                     | Multimax MP 513 |
| Valid rim size                    | 11 x 18         |
| Rim connection                    | 6/161/205       |
| Bolt hole design                  | A2              |
| Offset (mm)                       | +20             |
| Rim colour                        | Silver          |
| Load capacity complete wheel [kg] | 2060            |
| Speed complete wheel [km/h]       | 40              |
| RDRA (Reifendruckregelanlage)     | No              |
| RDKS (Reifendruckkontrollsystem)  | No              |



## Technical Informations

|                            |            |
|----------------------------|------------|
| Assembly Item no. Tyres    | • 15735226 |
| LI / SI / PR               | 133 G      |
| Load capacity 1 [kg]       | 2060       |
| Speed 1 [km/h].            | 90         |
| Direction                  | Right      |
| Antistatic                 | No         |
| Tyre colour                | Black      |
| Nettogewicht [kg] (gültig) | 78,28      |
| ECE regulation number      | ECE 54     |

|                                |                               |
|--------------------------------|-------------------------------|
| Section width (mm)             | 360                           |
| Stat. radius (SLR) [mm]        | 448                           |
| Rolling circumference [mm].    | 2954                          |
| Tread depth (mm)               | 28,5                          |
| Number of lugs                 | 18x2                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 33060119                    |
| Load capacity of rim 1 [kg]    | 3850                          |
| Speed Rims 1 [km/h]            | 40                            |
| Load capacity of rim 2 [kg]    | 2350                          |
| Speed Rims 2 [km/h]            | 80                            |
| Maximum speed [km/h].          | 40                            |
| Maximum air pressure [bar].    | 3,75                          |
| Number of bolt holes           | 6                             |
| hub hole diameter [mm].        | 161                           |
| Bolt hole circle diameter [mm] | 205                           |
| Bolt hole diameter [mm]        | 21.5                          |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R16                           |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | kein Hump                     |
| Valve protection               | VSH                           |
| Single / multi-part            | einteilig                     |
| Rim centering                  | BC                            |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |

---

|                          |                |
|--------------------------|----------------|
| Disc thickness [mm]      | 12.0           |
| Ventilation holes        | No             |
| Verschweißung beidseitig | No             |
| Valve seat               | External Valve |
| Valve hole diameter [mm] | 15.7           |
| Preassembled valve       | No             |
| TPMS-kompatibles Ventil  | No             |
| Valve design             | Metal valve    |
| Valve designation ETRTO  | V5.01.1        |
| Valve length [mm]        | 50.0           |
| Valve angle [°]          | gerade         |